

ShinFlow

Airflow Built for You
あなたを知る風へ

I-series

AI SMART INVERTER



HUMAN
SENSING



VOICE
CONTROL

OFFLINE



QUIET
AIR



UVC



AI Digital
Ambassador

Lisa

ULTIMATE CARE

365 DAYS

1 to 1
Exchange



ShinFlow Japan
R&D Center

HUMAN SENSING

Radar sensing finds you up to 5 metres away, steers the air your way, and eases off when you leave



Comfort airflow wherever you are



Indirect airflow for ultimate comfort



Detects occupancy for smarter energy savings



AI ECO

An onboard AI chip learns your patterns and tunes the cooling in real time, for up to **40% energy saving** against standard inverter mode

VOICE CONTROL

OFFLINE

Responds to both Bahasa Melayu and English, with no internet connection needed. Your voice is the remote, up to 5 metres away

SOFTWARE UPDATE

Connect to Wi-Fi and the unit updates its own software over the air, adding improvements and fixes without a service visit

99.9% UVC PURIFICATION

A built-in UVC light purifies the air as it passes through, clearing away 99.9% of bacteria, viruses and mould

QUIET AIR


ShinFlow AC **19dB(A)**

Runs as low as **19dB(A)**, quieter than rustling leaves. Perfect for light sleepers and quiet rooms

Specification

Model	Indoor Unit Outdoor Unit		SW09IAA4DI-5 S09IAA4DI-5	SW12IAA4DI-5 S12IAA4DI-5
Cooling Capacity	Rated (Min~Max)	Btu/h	9900(3070-13600)	12200(4090-13600)
Power Consumption		W	650 (240-1450)	850 (240-1450)
Running Current		A	3 (0.9-4.0)	4 (0.9-6.6)
CSPF (Cooling Seasonal Performance Factor)		Wh/Wh	6.15	6.50
Energy Efficiency Star Rating				
Power Supply		V,HZ,Ph	220-240V~ / 50Hz	
Indoor Unit	Indoor Air Flow (H)	m3/h(cfm)	630 (370)	680 (400)
	Indoor Sound Level (H/M/L)	dB(A)	39/31/19	39/31/19
	Dimension	width	765	825
		depth	217	217
		height	320	320
Weight	kg	9.5	10	
Outdoor Unit	Outdoor Sound Level	dB(A)	45	46
	Dimension	width	711	711
		depth	280	280
		height	538	538
	Refrigerant Charge	g	R32/540g	R32/540g
Weight	kg	23	23	
Refrigerant Piping	Liquid/Gas Pipe Size	mm(inch)	Φ6.35/Φ9.52 (1/4"/3/8")	Φ6.35/Φ9.52 (1/4"/3/8")
Indoor-Outdoor Connection Wiring (Not Included)			4x1.0 mm ²	4x1.0 mm ²
Power Supply Wiring (Not Included)			3x1.0 mm ²	3x1.0 mm ²
Thermostat Type			Wireless Remote Control / Built-In Wi-Fi	

INCLUDED COMPONENTS



Indoor Unit



Outdoor Unit



Remote Controller

ShinFlow Malaysia

Unit No. T1-L 16, Tower 1, Level 16, PJ33, Jalan Professor Khoo Kay Kim, Seksyen 13, 46200 Petaling Jaya, Selangor.

Contact Number : 03 - 7932 1188

ShinFlow



www.shinflow.com